



Powder Free Extra Length Ambidextrous Non-Sterile 26 cm Nitrile Gloves with Textured Fingertips

PPE Category III (Complex Design) according to Council Directive 89/686/EEC

Fully compliant to the latest PPE norms – EN 374:2003 "Protective gloves against chemicals and micro-organisms"

PRODUCT INFORMATION

Size	Catalogue Numbers	Applicable Norms with Pictograms			
Extra Small (XS/6)	67 6231	EN 374:2003	EN 374:2003		
Small (S/7)	67 6232		Level 3 C C 0120*	((
Medium (M/8)	67 6233			0120*	
Large (L/9)	67 6234	EN 420:2003 + A1:2009			
Extra Large (XL/10)	67 6235	Also meets or exceeds EN 455-1:2000, EN 455-2:2015, EN 455-3:2015 & EN 455-4:2009 relating to Council Directive 93/42/EEC for Medical Devices			

^{*} SGS UK Ltd (Notified Body No: 0120), Unit 202B Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

Material: Proprietary multi-polymer formulation (Acrylonitrile Butadiene with blend of polychloroprene), based on

twinSHIELD™ technology. Contains no natural rubber latex.

Design: Double barrier protection afforded by orange outer layer combined with white inner-lining.

Ambidextrous, beaded cuff and with textured fingertips.

Packaging: Ninety (90) gloves per dispenser. Dispenser is varnished for enhanced compatibility with laboratory

environments. Gloves are flat-packed. Ten (10) dispensers per case. Packed in a reinforced single-

walled shipping case.

6.0N, min.

PHYSICAL PROPERTIES

- After Accelerated Aging

Characteristics	Value	Test Method					
Freedom from holes	<0.65 AQL ¹	EN 374:2003					
¹ AQL as defined per ISO 2859 for sam	npling by attributes						

Tensile Properties

Tensile Strength (min) Typical

Before Aging

6.0N, min.

7.0N

500%, min.

EN 455-2:2015, ASTM D573-04(2015) and ASTM D412-15a

400%, min.

8.0N

Dimensional	Measured Point	Mm	mil	
- Nominal Thickness	Middle Finger	0.17	6.6	ASTM D3767-03(2014)
	Palm	0.14	5.5	
	Cuff	0.10	4.0	
- Length	260mm, min.		265mm, typical	EN 420:2003 + A1:2009

Palm Widths

- Nominal Width (mm)	XS/6	S/7	M/8	L/9	XL/10	EN 455-2:2015
	≤80	85	95	105	≥110	

Hand Circumference

- Nominal circumference (mm)	XS/6	S/7	M/8	L/9	XL/10	EN 420:2003 +A1:2009
	152	178	203	229	254	

ADDITIONAL DATA

- Biocompatibility demonstrated by Buehler and Primary Skin Irritation Tests.
- Non-detectable levels of chemical allergens using aqueous solution extraction (Phosphate buffered solution) and High Performance Liquid Chromatography (HPLC) assay method for quantitative analysis.
- Accelerator-free to minimize the risk of Allergic Contact Dermatitis (also known as Type IV, Delayed Hypersensitivity or Chemical Allergy).
- **Powder free** to minimize the potential consequences of powder-borne dermatitis. Residual powder content is 1.0 mg/glove (typical) with a limit of 2.0 mg/glove (ISO 21171:2006 "Medical gloves Determination of removable surface powder").
- **Micro organism and virus resistant** passes highest level of micro organism resistance per EN 374-2:2014 (Performance level 3, AQL <0.65 and inspection level G1 according to 1000ml water test) and passes viral penetration test using Phi-X174 bacteriophage (ISO 16604:2004 Procedure B & ASTM F1671-97b).
- Tested for electrostatic properties according to EN 1149-1/2/3 & 5.
- Extensively tested for chemical permeation according to EN 16523-1:2015 (please refer to chemical resistance guide on website www.shieldscientific.com/public/chemical-resistance-guide).

QUALITY SYSTEMS

• Manufactured in accordance with ISO 9001:2015 and ISO 13485:2016.

"SHIELDskin™, A revolution in Glove Technology"



www.shieldscientific.com